



Papillon Paints

We paint your dreams

Brilliant Wallcare Putty

Product No. 1008

Brilliant wall putty is a white cement based Exterior & Interior smooth wall putty formulated with exceptional polymers and functional additives.

USES

Used as Putty / Filler to fill the unevenness and dents on the surface. Shall be applied on prepared masonry concrete, plaster, gypsum & Wood surfaces.

PROPERTIES

Appearance

Flat.

Color

Milky White.

Pack Size

20 Kgs. & 40 Kgs.

Spreading Rate

7 – 8 Sq. ft./kg./mm. Actual spreading rate depending on surface texture, porosity and application method.

Drying Time

Surface dry in 1 hour. Re-coatable after 8 – 10 hours (in normal drying conditions).

Pot life

3 – 4 hours (in normal drying conditions).

Shelf Life

3 months minimum in original sealed bags, with proper storage conditions.

APPLICATION DATA

Apply by putty knife. For details of spray equipment contact Papillon Paints Technical Services Department.

Thinning

30 – 35% by volume with potable water.

Cleaning

Clean all tools and equipment immediately after use with clean water.

Caution

Do not use when humidity levels may cause surface condensation (maximum 85%), during rainy conditions or if temperatures are likely to fall below 5°C during application and drying. Protect from frost.

SPECIFICATION

Surface Preparation & Directions of use (Interior / Exterior)

- i. Sand the surface with Emery paper 180 to remove the loose, cracked or flaked paint, paint dust etc.
- ii. Apply one coat of Papillon Paints Primer to bare areas or overlapping onto existing decoration. Allow to dry for 6 – 8 hours.
- iii. Surfaces of high porosity (very chalky and powdery) should be primed with two coats of Papillon Paints Primer.
- iv. Smoother the surface by filling small cracks, surface imperfections and dents with thin coat of Papillon Paints Brilliant Wallcare putty. Allow to dry for 8 - 10 hours. Sand with Emery paper 180 and remove the dust by wipe clean.
- v. Apply one coat of Papillon Paints Primer and allow to dry for 4 - 6 hours.
- vi. Light sand with Emery paper 320 / 400 and remove the dust by wipe clean.
- vii. Topcoat: For interior surfaces, apply Papillon paints, Interior Emulsions. For Exterior surfaces, apply Papillon Paints Exterior Emulsion.

See notes [i, iii, iv].

Preparation (Previously Decorated)

All surfaces should be sound, clean, dry and free from loose and flaking material, dirt, efflorescence, oil, grease, wax, polish etc. Where necessary spot prime with the relevant Papillon Paints Universal Primer, and where appropriate fill dents, small cracks and surface imperfections with of Papillon Paints Brilliant Wallcare putty. Large cracks may be filled with proprietary Acrylic Sealant.

See note [ii].

NOTES

- i. Organic growth (fungus, mildew etc.) on the surfaces should be treated with a proprietary fungicidal treatment in accordance with manufacturer's instructions.
- ii. Alkyd based and gloss painted surfaces should be thoroughly washed and rubbed down before painting. For further advice contact Papillon Paints Technical Services Department. .
- iii. A third coat topcoat may be required if there is a marked color contrast between the surface and the paint to be applied.
- iv. Surfaces of high porosity (very chalky and powdery) should be primed with two coats of Papillon Paints Universal Primer.
- v. Two coats will be required on internal surfaces if Papillon Paints Universal Primer is to be used as primer and undercoat.

SAFETY INFORMATION

Use only in well ventilated areas. In case of insufficient ventilation during spraying, wear suitable respiratory equipment. Do not breathe vapor / spray. In case of contact with eyes, rinse immediately with plenty of sweet water and seek medical advice. Keep out of reach of children.